


Soundproofing Underlay



Silentstep® is a new generation of acoustic carpet underlay, comprising a flexible mass-loaded barrier, fused onto a high density premium foam underlay. The combination of these two products allows **Silentstep** to reduce the transmission of footfall and impact-generated noise.

Silentstep was developed to meet market noise reduction requirements in multi-storey living, commercial, automotive and marine markets.

Easy to cut and lay, it offers excellent support and a firm cushioned base for all types of carpet applications. It is ideally suited for lightweight flooring constructions such as timber and marine applications where fibreglass and composite floor panels are used.

When laying carpet over a floor constructed using lightweight timber and joists, typical standard underlay offers little effect in reducing the transmission of footfall and impact noise.

Silentstep isolates the barrier layer from the floor structure, increasing the performance of the floor system between two rooms. This feature means that critical frequencies generated during speech and electronic audio technologies such as radio and television etc can be reduced.

Silentstep products are environmentally safe, contain no ozone-depleting substances and comply with European and Australian standards for Volatile Organic Compound emissions.

FEATURES


- Bonded foam is made from 100% recycled material
- No ozone-depleting substances are generated during manufacture
- Free from lead, odour-producing oils and bitumen
- Easily installed by quality carpet layers. No special tools or fixtures required
- Uses specially made, high density, high rebound bonded foam as the impact layer
- Long service life, will not degrade like rubber underlay
- Foam is treated with Ultra-Fresh® to resist mould, mildew, bacterial growth and dust mites
- Available in roll or sheet form, or custom made to suit (minimum order quantities apply)
- Standard barrier weight 4kg/m². Other weights available on request, subject to minimum order quantities

APPLICATIONS

- Multi-storey living areas constructed from lightweight materials with the intention to lay carpet
- Placed under solid timber or parquet flooring using Pyrotek's flooring systems - contact your local Pyrotek Representative
- Marine vessels to stop engine noise travelling into staterooms, salons, VIP cabins etc
- Transport industry; under automotive, firewalls, wheel arches, boot mats, and transmission tunnels
- Motor homes and luxury motor coaches

IMPACT NOISE REDUCTION


(Tested at CSIRO INSS 21031 - Rev B to ISO 140/7)



Frequency (Hz)	Bare timber floor	Timber Floor with Silentstep
100	81	67
125	82	63
160	86	64
200	85	62
250	86	55
315	87	51
400	86	51
500	87	50
630	89	47
800	90	47
1000	89	46
1250	87	45
1600	86	46
2000	85	44
2500	84	43
3150	83	42

TRANSMISSION LOSS

(Tested to ISO 15186-1/ISO 10140-4 (Report No. 188))



Frequency (Hz)	Silentstep
100	10.58
125	13.21
160	19.47
200	17.24
250	18.82
315	20.19
400	22.20
500	23.24
630	25.36
800	26.79
1000	29.69
1250	31.41
1600	31.79
2000	32.62
2500	35.10
3150	38.41
4000	41.12
5000	44.04
STC/Rw	28

PRODUCT SPECIFICATIONS

COMPOSITE WEIGHT (kg/m ²)	THICKNESS (mm)	ROLL WIDTH (mm)	ROLL LENGTH (Lineal Metres)	ROLL WEIGHT (kg)	FLAMMABILITY PROPERTIES (FMVSS-302)	OPERATING TEMPERATURE RANGE (°C)
5	9	1350	5	34	Self Extinguishing	-40 to 100 (Continuous) -40 to 120 (Intermittent)

Tolerances: Length: -0/+30mm; Width: -0/+3mm; Thickness: +/- 2mm; Weight: +/- 5%

ACOUSTIC PROPERTIES

L _n T _w + C ₁	L _{n,w}	IIC	R _w	AAAC rating
56	56	54	28	4 Star