



Soundblock Solutions™ Noise Barriers Product Data Sheet NuWave Underlay

Most commonly used to silence noise for timber flooring, particularly laid over wooden joist for timber floors or alternatively laid under carpet as an underlay. NuWave Underlay is an acoustic underlay to reduce noise transfer in both single and multi storey dwellings.



Product:

Polyester fabric backed, heavy flexible vinyl like limp mass polymer incorporating a factory applied open cell polyurethane foam for carpet or closed cell polyethylene foam for timber.

Specifications:

CARPET UNDERLAY	STOCKCODE	Weight M2	Width	Roll Length
Nuwave "Carpet Underlay" Fabric Backed Flexible Noise Barrier Supplied in Rolls				
STC/Rw rating 26	312080423000	4kg/m ²	1.35m	5m
STC/Rw rating 29	312080633000	6kg/m ²	1.35m	3m
STC/Rw rating 30	312080843000	8kg/m ²	1.35m	3m
TIMBER FLOORING UNDERLAY	STOCKCODE	Weight M2	Width	Roll Length
Nuwave " Underlay" Fabric Backed Flexible Noise Barrier Supplied in Rolls				
STC/Rw rating 26	312080423000	4kg/m ²	1.35m	5m

We also have a range of impact noise isolation product for floating timber floors on concrete and sound isolation in concrete flooring.



LIGON 216 PTY LTD ABN 79 003 799 068 trading as **SOUNDBLOCK SOLUTIONS**
P. O. Box 813, Woollahra NSW 1350
Tel: 61 2 9327 7410 Fax: 61 2 9327 1077 Mobile: 0418 409 504
Website: www.soundblock.com.au Email: management@soundblock.com.au